

NO	DESCRIPTION OF REVISIONS	MADE BY	DATE
\odot	RE-ISSUE	L. LOPEZ	2/02
(2)			
(B)			
(0)			






EXTRUDED T-SECTION BACK BRACING

NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES, EXCEPT AS NOTED.
- SIGNS LESS THAN 48" HIGH AND 144" WIDE SHALL BE MADE OF A SINGLE SHEET OF ALUMINUM.
- SIGNS LESS THAN 144" HIGH SHALL HAVE NO HORIZONTAL JOINTS.
- 4. SIGNS OVER 144" HIGH MAY HAVE HORIZONTAL AND VERTICAL JOINTS; HOWEVER, NO SHEET SHALL BE LESS THAN 18" WIDE OR 18" HIGH.
- 5. ALL HORIZONTAL JOINTS SHALL OCCUR AT AN EXTRUDED T-SECTION.
- ALL SCREWS, BOLTS, AND LOCKWASHER SHALLS BE OF ALUMINUM ALLOY, STAINLESS STEEL, OR CADMIUM PLATED STEEL.
- 7. ONLY ALUMINUM RIVETS SHALL BE USED.



SHEET 3 OF 4 NOT TO SCALE

ARIZONA DEPARTMENT OF TRANSPORTATION INTERMODAL TRANSPORTATION DIVISION STANDARD DRAWINGS

ALUMINUM EXTRUSION PANEL INSTALLATION DETAIL

S-8

2/02